



3 L



Belt Ref:	La (mm)		
DRY-3L-110	K		279
DRY-3L-120	K		305
DRY-3L-130	K		330
DRY-3L-140	K		356
DRY-3L-150	K		381
DRY-3L-160	K		406
DRY-3L-170	K		432
DRY-3L-180	K		457
DRY-3L-190	K		483
DRY-3L-200	K		508
DRY-3L-210	K		533
DRY-3L-220	K		559
DRY-3L-230	K		584
DRY-3L-240	K		610
DRY-3L-250	K		635
DRY-3L-260	K		660
DRY-3L-270	K		686
DRY-3L-280	K		711
DRY-3L-290	K		737
DRY-3L-300	K		762
DRY-3L-310	K		787
DRY-3L-320	K		813
DRY-3L-330	K		838
DRY-3L-340	K		864
DRY-3L-350	K		889
DRY-3L-360	K		914
DRY-3L-370	K		940
DRY-3L-380	K		965
DRY-3L-390	K		991
DRY-3L-400	K		1016
DRY-3L-410	K		1041
DRY-3L-420	K		1067
DRY-3L-430	K		1092
DRY-3L-440	K		1118
DRY-3L-450	K		1143

Belt Ref:	La (mm)		
DRY-3L-460	K		1168
DRY-3L-470	K		1194
DRY-3L-480	K		1219
DRY-3L-490	K		1245
DRY-3L-500	K		1270
DRY-3L-510	K		1295
DRY-3L-520	K		1321
DRY-3L-530	K		1346
DRY-3L-540	K		1372
DRY-3L-550	K		1397
DRY-3L-560	K		1422
DRY-3L-570	K		1448
DRY-3L-580	K		1473
DRY-3L-590	K		1499
DRY-3L-600	K		1524
DRY-3L-610	K		1549
DRY-3L-620	K		1575
DRY-3L-630	K		1600
DRY-3L-640	K		1626
DRY-3L-650	K		1651
DRY-3L-660	K		1676
DRY-3L-670	K		1702
DRY-3L-680	K		1727
DRY-3L-690	K		1753
DRY-3L-700	K		1778
DRY-3L-710	K		1803
DRY-3L-720	K		1829
DRY-3L-730	K		1854
DRY-3L-740	K		1880
DRY-3L-750	K		1905
DRY-3L-760	K		1930
DRY-3L-770	K		1956
DRY-3L-780	K		1981
DRY-3L-790	K		2007

- Large Diameter KEVLAR cord impregnated with special compound eliminates the need for re-tensioning while offering:
 - High tensile strength
 - Non-extensibility
 - High resistance to shock loads
 - DOUBLE WRAP of special fabric ensures:
 - High resistance to wear and tear
 - Reduced slippage while clutching
 - Belt Characteristics ensure:
 - High resistance to repeated reverse flexing
 - High resistance to Oil, Heat and Cracking
- EXTENSIVE RANGE tested and approved by

