

HSS-Co Bihart cobalt hacksaw blade

This globally unique all-cobalt-alloy HSS steel safety blade has four hardness zones each with the optimum properties: extreme tooth hardness (65 HCR), soft tooth bed to prevent the teeth from breaking off and a blade body which is extremely elastic and stable. The special set of each tooth prevents clamping in the work piece.




Packing unit: 100 blades per carton (10 x 10 pieces)



Dimensions		Tooth spacing		Packing unit loose per carton	Part no.
mm	approx. inch	teeth inch	teeth cm		
300 x 13 x 0.65	12 x 1/2 x 0.025	18	8	100	R312130018
300 x 13 x 0.65	12 x 1/2 x 0.025	24	10	100	R312130024
300 x 13 x 0.65	12 x 1/2 x 0.025	32	12	100	R312130032

HSS bi-flexible hacksaw blade

Due to a special heat treatment, this new HSS all-steel blade combines the apparently incompatible properties - hardness and elasticity. Because this blade has two hardness zones, it has the properties of a bi-metallic blade with set teeth - the ideal blade for the craftsman.



Packing unit: 100 blades per carton (10 x 10 pieces)



Dimensions		Tooth spacing		Packing unit loose per carton	Part no.
mm	approx. inch	teeth inch	teeth cm		
300 x 13 x 0.65	12 x 1/2 x 0.025	18	8	100	R318130018
300 x 13 x 0.65	12 x 1/2 x 0.025	24	10	100	R3181300R4
300 x 13 x 0.65	12 x 1/2 x 0.025	32	12	100	R318130032

Record V power-saw blade

This proven industrial blade is especially suitable for all modern hydraulic power hacksaws and machines used for sawing high-alloy and stainless steels. The vacuum hardening treatment imparts exceptional hardness to the teeth and gives the blade a long service life.



Dimensions		Tooth spacing		Packing unit loose per carton	Part no.
mm	approx. inch	teeth inch	teeth cm		
300 x 25 x 1.25	12 x 1 x 0.05	10	4	10	R3530251210
300 x 25 x 1.25	12 x 1 x 0.05	14	6	10	R3530251214
350 x 25 x 1.25	14 x 1 x 0.05	10	4	10	R3535251210
350 x 25 x 1.25	14 x 1 x 0.05	14	6	10	R3535251214
400 x 25 x 1.25	16 x 1 x 0.05	10	4	10	R3540251210
400 x 25 x 1.25	16 x 1 x 0.05	14	6	10	R3540251214
450 x 32 x 1.60	18 x 1 x 0.05	10	4	10	R3545321610
450 x 32 x 1.60	18 x 1 x 0.05	14	6	10	R3545321614