



Luna compressors

A range of European produced, professional quality, compressors with a choice of 230 volt single phase and 400 volt three phase machines covering 2.5hp through to 10hp with free standing and portable models. All regular Luna compressors are supplied as standard with synthetic oil.

When choosing the correct capacity compressor it is important to take in to account the likely air consumption of the tools being used. As a guideline, based on common practice, the likely intermittence of different types of machines is as follows –

50%	die grinders and grinding machines
40%	air saws and nibblers
30%	chipping and needle hammers
20%	air drills and blow guns
15%	impact wrenches, air ratchets and spray guns

For all Luna air tools the tested air consumption at various intermittences and based on a pressure of 6.2 bar or 90psi is shown in the catalogue. At 100% intermittence the air consumption is measured with the trigger pulled for one minute, at 15% the trigger is pulled for 15% on one minute and so on.

A complete range of hoses and connectors, air tools and lubricants is also available – full details can be found in the Air Tools section of this catalogue



2.5HP compressor

Portable, single stage reciprocating compressor with air tank and direct drive motor. Suitable for spraying, cleaning, inflating tyres etc. Equipped with miniature circuit breaker that trips with an overload, reset manually. Supplied complete with motor, rubber lead with plug, pressure switch, regulator with pressure gauge and quick couplings.

Stock no	206346108
Compressor block	1 stage
Motor voltage	V 230 1 phase
Fuse (slow)	A 10
Displacement	l/min 270
Displacement	l/sec 4.5
Free air displacement	l/min 197
Free air displacement	l/sec 3.25
Max working pressure	bar 8
Air container volume	l 24
Sound level	dB (A) 84
Motor output	KW (hp) 1.9 (2.5)
Compressor block speed	r/min 2850
Dimensions LxWxH	mm 600x260x600
Weight	kg 21
Price	POA

At 6 bar





3HP compressor



Portable, single stage reciprocating compressor with air tank and direct drive motor. Suitable for spraying, cleaning, inflating tyres etc. Equipped with miniature circuit breaker that trips with an overload, reset manually. Supplied complete with motor, rubber lead with plug, pressure switch, regulator with pressure gauge and quick couplings.



Stock no	206766107	
Compressor block	1 stage	
Motor voltage	V	230 1 phase
Fuse (slow)	A	16
Displacement	l/min	450
Displacement	l/sec	7.50
Free air displacement	l/min	317
Free air displacement	l/sec	5.28
Max working pressure	bar	8
Air container volume	l	24
Sound level	dB (A)	77
Motor output	kW (hp)	2.2 (3)
Compressor block speed	r/min	2850
Dimensions LxWxH	mm	620x600x92
Weight	kg	44
Price	POA	

At 6 bar

3, 4 and 5HP Portable compressors

Portable, reciprocating compressor with air tank and direct drive motor. Fully automatic operation which means automatic start and stop. A reliable and well balanced design with effective cooling and highly efficient. The unit is equipped with a relief valve which is also controlled by a push bar switch in order for the compressor to start without a back pressure in the cylinders. Suitable for spraying, cleaning, inflating tyres etc. Equipped with miniature circuit breaker that trips with an overload, reset manually. Supplied complete with motor, mains cord with plug, pressure switch, safety valve, pressure gauge, regulator and quick couplings.



Stock no	206746000	206746109	206756208
Compressor block	1 stage	1 stage	2 stage
Motor voltage	V 230 1 phase	400 3 phase	400 3 phase
Fuse (slow)	A 16	16	20
Displacement	l/min 308	449	578
Displacement	l/sec 5.13	7.48	9.63
Free air displacement	l/min 216	314	462
Free air displacement	cfm 7.63	11.09	16.31
Max working pressure	bar 9	9	9
Air container volume	l 50	90	100
Sound level	dB (A) 77	79	74
Motor output	kW (hp) 2.2 (3)	3 (4)	4 (5.5)
Compressor block speed	r/min 1400	1400	1400
Dimensions LxWxH	mm 800x380x700	1000x400x800	1050x400x830
Weight	kg 55	75	80
Price	POA	POA	POA

At 6 bar

1.5HP Oil Free Compressor

Portable single stage, oil free reciprocating compressor with an air tank and direct drive motor. Suitable for spraying, cleaning, inflating tyres and other minor maintenance work. Equipped with a miniature circuit breaker that trips when overloaded which can be reset manually. Supplied complete with motor, rubber lead with plug, pressure switch, regulator with pressure gauge and quick couplings.



Stock no	207566001	
Compressor block	D8 oil free 1 stage	
Motor voltage	V	230 1 phase
Fuse (slow)	A	10
Through put cylinder volume	l/min	190
Through put cylinder volume	l/sec	3.17
Free air displacement	l/min	115
Free air displacement	cfm	4.06
Max working pressure	bar	8
Air container volume	l	24
Sound level	dB (A)	81
Motor output	kW (hp)	1.1 (1.5)
Compressor block speed	r/min	2850
Dimensions LxWxH	mm	600x260x600
Weight	kg	20
Price	POA	

At 6 bar

All prices exclude VAT and are subject to availability



5.5, 7.5, and 10HP Stationary Compressors

Stationary, two stage reciprocating compressor for fully automatic operation, which means automatic start and stop. The cylinder block is made of cast iron. A reliable and well balanced design with effective cooling and highly efficient. The unit is equipped with a relief valve which is also controlled by a pressure switch, in order for the compressor to start without a back pressure in the cylinders. Suitable for larger garage workshops, industries, agriculture etc, where the need of air is great. Equipped with a miniature circuit breaker that trips when overloaded. Reset automatically. Supplied complete with air tank, pressure switch, safety valve and pressure gauge.

Stock no		206786006	206786105	206786204
Compressor block		K25 2 stage	K30	K50
Motor voltage	V	400 3 phase	2 stage 3 phase	2 stage 3 phase
Fuse (slow)	A	16	20	25
Through put cylinder volume	l/min	578	727	1074
Through put cylinder volume	l/sec	9.63	12.11	17.90
Free air displacement	l/min	462	582	859
Free air displacement	cfm	16.31	20.55	30.34
Max working pressure	bar	10.5	11	11
Air container volume	l	150	200	270
Sound level	dB (A)	74	74	76
Motor output	kW (hp)	4.5 (5.5)	5.5 (7.5)	7.5 (10)
Compressor block speed	r/min	1400	1000	1000
Dimensions LxWxH	mm	1380x440x950	1420x420x1100	1700x600x1370
Weight	kg	91	109	186
Price		POA	POA	POA

At 6 bar



Compressor oil

This compressor oil is recommended for all types of stationary and mobile engines and marine diesels used for coastal shipping, but can also be used with hydraulic systems, screw compressors, converters, etc where a single grade engine oil is required.

Stock no		155320104	155320203
Viscosity at 40°C	mm ² /s	98	98
Viscosity at 100°C	mm ² /s	10.5	10.5
Capacity	l	1	3
Pack		Can	Can
Price		€8.30	€21.80



This compressor oil is recommended for all types of stationary reciprocating compressors. The oil is based on highly refined mineral oil with additives against rust, corrosion and foaming.

Stock no		155340102	155340201
Viscosity at 40°C	mm ² /s	100.3	100.3
Viscosity at 100°C	mm ² /s	9.8	9.8
Viscosity index		69	69
Capacity	l	1	5
Pack		Can	Can
Price		€9.30	€38.90



Air Tool oil

This air tool oil is a white oil, based on mineral oil without any additives. The oil can be used as an air and mist lubrication oil for rotating tools where requirements on optimal cleanliness are essential. The oil is refined for use such as a softening agent within the chemical engineering industry. The oil is odourless and does not discolour.

Stock no		155300106	155300205
Viscosity at 40°C	mm ² /s	15.0	15.0
Viscosity at 100°C	mm ² /s	3.4	3.4
Viscosity index		34.0	34.0
Capacity	l	1	3
Pack		Can	Can
Price		€9.00	€24.20





Air Tool oil

Pneumatic tool oil gives an improved working environment and gives minimum wear to the lubrications systems components, compared with conventional air tool oil. Also recommended for industrial and some mobile hydraulic applications. The oil is recommended within the temperature range -25° C to 70° C



Stock no		155310105	155310204	155310303
Viscosity at 40°C	mm ² /s	22	22	22
Viscosity at 100°C	mm ² /s	4.2	4.2	4.2
Viscosity index		80	80	80
Capacity	l	1	3	5
Pack		Can	Can	Can
Price		€10.90	€29.90	€46.90

Air hose reel



8 meter PVC air hose reel with PP housing with 180° rotating wall or roof fixing and automatic hose return and automatic stop at required length. Internal hose diameter 8mm suitable for use up to 12 bar. Also suitable for hot and cold water. Includes 36" lead in hose. Dimensions 360x180x380mm, weight 5.8 kilos.



Stock No	PRICE
756200705	€85.00



15 meter PVC air hose reel with PP housing with 180° rotating wall or roof fixing and automatic hose return and automatic stop at required length. Internal hose diameter 10mm/3/8" suitable for use up to 20 bar. Also suitable for hot and cold water. Includes 36" lead in hose. Dimensions 480x230x490mm, weight 9.0 kilos.



Stock No	PRICE
756200707	€89.90

Hose Reels

Hose reel adapted for vehicle workshops and industry with demands on trouble free usage, equipped with a pivoted wall or roof bracket which simplifies handling. The hose lengths are controlled by a catch that comes into effect with each extended 1/2 meter and which can be disengaged if the function isn't required. Made of double layered polyurethane, a hard wearing and adaptable hose that does not twist but keeps its straight structure even when fully extended. The hose is only intended for compressed air and must not be used for gases, etc. Swivels through 300°. Temperature range -5 - +40° C.



Stock No	205810104	
Hose material		PU
Hose dimension internal	inch	5/16" x 1/2"
Hose dimension internal	mm	8 x 12
Hose length	m	7 (6+1)
Max. working pressure	bar	12
Connection thread	R	1/4"
Temperature range	°C	-5 - +40°
Weight	kg	7.0
Price		€225.00



Hose Reels

A heavy duty design makes it suitable for vehicle workshops and industry. Fitted with a rewinder making the workplace more safer without twisted cord coils. Equipped with a pivoted wall or roof bracket which simplifies handling. The hose lengths are controlled by a catch that comes into effect with each extended 1/2 meter and can be disengaged if the function isn't required. A hard wearing adaptable hose made of double layered polyurethane. The hose is only intended for compressed air and must not be used for gases, etc. Temperature range -5 - +40 °C.

Stock no	208390104	
Hose material	PU	
Hose dimension internal	inch	3/8
Hose dimension internal	mm	10
Hose length	m	13 (12+1)
Max. working pressure	bar	12
Connection thread	R	3/8
Temperature range	°C	-5 - +40°
Weight	kg	7.0
Price	€395.00	



Suitable for workshops and industrial applications, a heavy duty design made of resistant plastic. It has an integral handle which can be automatically folded up for use, the rewinder swivels 250°. A flexible and resistant PU hose both in warm and cold weather conditions. The hose retains its straight structure and does not twist when fully extended. After use the hose automatically rewinds slowly without the risk of damage and distributes itself in the housing by means of a movable hose guide. The hose is only intended for compressed air and must not be used for gases, etc. Temperature range -5 - +40°C.

Stock No	208040105	208040204
Hose material	PU	PU
Hose dimension internal/external	inch 5/16 x 1/2	3/8 x 7/62
Hose dimension internal/external	mm 8x12	10x14.5
Hose length	m 14 (12.5+1.5)	16 (15+1)
Max. working pressure	bar 12	12
Connection hose	m 2	2
Connection thread	R 1/4	3/8
Dimensions diameter x thickness	mm 310x130	380x180
Weight	kg 4.0	6.4
Price	€129.90	€165.00



A flexible PU hose that keeps its shape and doesn't get twisted even when it is fully extended and is suitable in combination with building compressors. Comes complete with swivelling 360° drum and air connection, drum fix screw, folding crank, manual reversible feed of the hose and an end cover of rigid plastic to prevent wear.

Stock No	208000109	
Hose material	PU	
Hose dimension internal/external	inch	5/16 x 1/2
Hose dimension internal/external	mm	8.5x12.5
Hose length	m	30
Max. working pressure	bar	17
Temperature range	°C	-5 - +40
Connection thread	G (R)	1/4
Dimensions Height x Width x Depth	mm	355x325x255
Weight	kg	9.7
Price	€120.00	





Swivelling Air Inlet Joint

A universal 360° swivelling, bi-directional air inlet joint. Ideal for keeping air lines straight and untwisted or for work in narrow spaces and gives greatly increased manoeuvrability of other air tools not fitted with a 360° swivelling air intake. Includes a plug for connecting the optional pressure gauge for monitoring in line air pressure or can be supplied complete with the pressure gauge as stock number 207510207.



Stock no		207510108	207510207	207510306
Air inlet	inch	¼	¼	¾
Air consumption*	l/min	750	750	1350
Air consumption*	cfm	26.5	26.5	47.7
Maximum working pressure	bar	10	10	10
Price		€15.40	€20.20	€15.40
Pressure gauge		207510504		
Price		€7.00		

Combined Filter, Regulator and Lubricators

Designed to filter the compressed air, to regulate the secondary pressure and to provide oil mist lubrication. Supplied with a pressure gauge as standard. Will remove up to 96% of water and particles of 5 micron or more from the air line supply to prevent corrosion and malfunction of machines and pneumatic components. Available with manual or automatic drains.



Manual Drain				
Stock no		204530109	204530208	204530307
Air inlet	inch	¼	¾	½
Rated flow min/max	l/min	15/550	50/2000	130/4000
Maximum pressure	bar	10	10	10
Minimum pressure by auto drain	bar	1	1	1
Bowl capacity	cm³	25	50	130
Adjustable working pressure	bar	0.5-8.5	0.5-8.5	0.5-8.5
Price		€49.90	€65.00	€85.00
Automatic Drain				
Stock no		204530406	204530505	204530604
Price		€64.90	€90.00	€115.00
Pressure gauge				
Stock no		207921008	207921008	207921107
Price		€8.10	€8.10	€8.10

Combined Filters and Regulators

Designed to filter the compressed air and to regulate the secondary pressure. Supplied with a pressure gauge as standard. Will remove up to 96% of water and particle of 5 micron or more from the air line supply to prevent corrosion and malfunction of machines and pneumatic components. Available with manual or automatic drains.



Manual drain				
Stock no		204520209	204520308	204520407
Air inlet	inch	¼	¾	½
Air consumption*	l/min	550	2000	4000
Maximum pressure	bar	10	10	10
Minimum pressure by auto drain	bar	1	1	1
Bowl capacity	cm³	15	20	45
Adjustable working pressure	bar	0.5-8.5	0.5-8.5	0.5-8.5
Price		€33.50	€52.00	€69.90
Automatic Drain				
Stock no		204520506	204520605	204520100
Price		€52.00	€69.90	€92.50
Interconnecting block				
Stock no		204501001	204501100	204501209
Price		€8.40	€12.60	€15.10
Bracket				
Stock no		204501308	204501407	204501506
Price		€4.70	€4.20	€5.90
Interconnecting block with bracket				
Stock no		204501605	204501704	204501803
Price		€5.70	€20.10	€22.00
Pressure gauge				
Stock no		207921008	207921008	207921107
Price		€8.10	€8.10	€8.10



Filters

Designed to remove up to 96% of water and particles of 5 micron or more from the air line supply to prevent corrosion and malfunction of machines and pneumatic components. Available with manual or automatic drains.

Manual Drain				
Stock no		204500102	204500201	204500300
Air inlet	inch	¼	¾	½
Air consumption*	l/min	550	1500	4000
Maximum pressure	bar	10	10	10
Minimum pressure by auto drain	bar	1	1	1
Bowl capacity	cm ³	15	20	45
Price		€17.10	€24.90	€33.10
Automatic drain				
Stock no		204500409	204500508	204500607
Price		€30.40	€54.40	€62.10
Interconnecting block				
Stock no		204501001	204501100	204501209
Price		€8.40	€12.60	€15.10
Bracket				
Stock no		204501308	204501407	204501506
Price		€4.70	€4.20	€5.90
Interconnecting block with bracket				
Stock no		204501605	204501704	204501803
Price		€5.70	€20.10	€22.00



Regulators

Designed to regulate working pressure when using pneumatic equipment with no reflow of the compressed air and a regulating knob which can be fixed in any position and a pressure gauge is included as standard.

Regulators				
Stock no		207920109	207920208	207920307
Air inlet	inch	¼	¾	½
Air consumption*	l/min	550	2500	6000
Maximum pressure	bar	10	10	10
Adjustable working pressure	bar	0.5-8.5	0.5-8.5	0.5-8.5
Bowl capacity	cm ³	15	20	45
Price		€21.70	€33.50	€44.70
Bracket				
Stock no		204501308	204501407	204501506
Price		€4.70	€4.20	€5.90
Interconnecting block with bracket				
Stock no		204501605	204501704	204501803
Price		€5.70	€20.10	€22.00
Pressure gauge				
Stock no		207921008	207921008	207921107
Price		€8.10	€8.10	€8.10





Oil Mist Lubricator

Designed to provide oil mist lubrication for pneumatic tools and components during use with an adjustable oil flow regulator and the facility to top up the oil even during use.



Stock no		204510101	204510200	204510309
Air inlet	inch	¼	¾	½
Max air consumption *	l/min	800	1700	5000
Min air consumption	l/min	15	50	130
Maximum pressure	bar	10	10	10
Bowl capacity	cm ³	25	50	130
Price		€19.90	€24.90	€36.90
interconnecting block				
Stock no		204501001	204501100	204501209
Price		€8.40	€12.60	€15.10
Bracket				
Stock no		204501308	204501407	204501506
Price		€4.70	€4.20	€5.90
interconnecting block with bracket				
Stock no		204501605	204501704	204501803
Price		€5.70	€20.10	€22.00
sight glass				
Stock no		204511000	204511208	204511208
Price		€1.60	€2.80	€2.80

Mini Oiler

Used in line on ¼" hose to keep Luna machines lubricated. All Luna air tools should be kept lubricated to prevent wear and rust. Be sure to use the correct pneumatic oil. (See page 451)



Stock No	Price
205710106	€7.70

Air Tool Accessories - European Specification

Steel sleeve and body of nickel plated brass. The couplings are single hand operated with a high flow capacity. Material selection and design make the couplings both robust and hard wearing. Nipples of zinc plated steel. Max. recommended working pressure: 15 bar. Air flow 1560 l/min. Temperature range: -20°C - +80°C. Interchangeable with Cejin 310-320 Rectus 23, 25, 26 and Tema 1600. Insert nipples in packs of 2.



119980100 & 126180207 type



119980506 & 126180504 type



119980803 & 126180801 type

Stock No.	Description	Price
119980100	Quick hose coupling ¼"	€10.70
119980209	Quick hose coupling ⅝"	€10.70
119980308	Quick hose coupling ¾"	€10.70
119980407	Quick hose coupling ½"	€12.30
119980506	Quick coupling male thread ¼"	€10.70
119980605	Quick coupling male thread ⅝"	€10.70
119980704	Quick coupling male thread ½"	€11.10
119980803	Quick coupling female thread ¼"	€10.70
119980902	Quick coupling female thread ⅝"	€10.70
119981009	Quick coupling female thread ½"	€11.80
119981108	Insert nipple hose coupling ¼"	€4.90
119981207	Insert nipple hose coupling ⅝"	€4.90
119981306	Insert nipple hose coupling ¾"	€4.90
119981405	Insert nipple hose coupling ½"	€5.80
119981504	Insert nipple male thread ¼"	€4.90
119981603	Insert nipple male thread ⅝"	€4.90
119981702	Insert nipple male thread ½"	€5.80
119981801	Insert nipple female thread ¼"	€4.90
119981900	Insert nipple female thread ⅝"	€4.90
119982007	Insert nipple female thread ½"	€5.80



Air Tool Accessories - UK Specification

Steel sleeve and body of nickel plated brass. The PLA quick couplings are single hand operated with a high flow capacity. Material selection and design make the couplings both robust and hard wearing. Nipples of zinc plated steel. Max. recommended working pressure: 15 bar. Air flow 1560 l/min. Temperature range: -20°C - +80°C. Insert nipples in packs of 2.

Stock No.	Description	Price
126180207	Quick hose coupling 1/4"	€5.40
126180306	Quick hose coupling 3/16"	€5.40
126180405	Quick hose coupling 3/8"	€5.40
126180504	Quick coupling male thread 1/4"	€5.40
126180603	Quick coupling male thread 3/8"	€5.40
126180702	Quick coupling male thread 1/2"	€5.70
126180801	Quick coupling female thread 1/4"	€5.40
126180900	Quick coupling female thread 3/8"	€5.40
126181007	Quick coupling female thread 1/2"	€5.70
126181205	Insert nipple hose coupling 1/4"	€2.60
126181304	Insert nipple hose coupling 3/16"	€2.60
126181403	Insert nipple hose coupling 3/8"	€2.60
126181502	Insert nipple male thread 1/4"	€2.60
126181601	Insert nipple male thread 3/8"	€2.60
126181700	Insert nipple male thread 1/2"	€4.00
126181809	Insert nipple female thread 1/4"	€2.60
126181908	Insert nipple female thread 3/8"	€2.60
126182005	Insert nipple female thread 1/2"	€4.80



Coiled air line hoses - UK specification

Ready to use hoses supplied with quick couplings in combination with oil resistant, polyurethane hose for maximal tightness, flexibility and life span. Sealing takes place with a cone and union nut, which together with the polyurethane hose, gives a sealed safe joint without hose clips. The couplings swivel through 360° to prevent the hose from twisting. High tear resistance give unique wear qualities. Unequalled aging characteristics - up to ten times longer life than conventional oil resistant rubber hose. Low weight, working pressure 11 bar. Flexible - always returns to its original shape. Maintains its flexibility during its entire life. High flow value. Temperature range: -20°C - +60°C.

Stock No.	Length m	Description	Internal diameter mm	External diameter mm	Price
126320100	2	coiled air hose	5.0	8.0	€15.30
126320209	4	coiled air hose	5.0	8.0	€17.30
126320308	2	coiled air hose	6.5	10.0	€17.90
126320407	4	coiled air hose	6.5	10.0	€20.60
126320506	6	coiled air hose	6.5	10.0	€26.30
126320605	4	coiled air hose	8.0	12.0	€24.90
126320704	6	coiled air hose	8.0	12.0	€29.50



Straight air line hoses - UK specification

Ready to use oil resistant, straight, polyurethane hose supplied with coupling and nipple. Temperature range: -20° - +60°C.

Stock No.	Length m	Description	Internal diameter mm	External diameter mm	Price
126330109	7.5	straight air hose	6.5	10.0	€22.20
126330208	7.5	straight air hose	8.0	12.0	€26.20
126330307	7.5	straight air hose	9.5	13.5	€37.90





Impact wrenches



Luna Impact Wrenches

Robust and powerful, reversible impact wrenches especially developed for professional workshop applications Luna air tools have been developed from the strong base established under the Race brand.

Just some of the features of the Luna range of impact wrenches –

- A choice of twin hammer or pin clutch
- A choice of hard wearing magnesium/aluminium or composite housings
- High torque action with three forward steps and reverse
- Handle exhausts
- Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose
- Stepless trigger
- Ergonomically designed rubber handle for better grip and insulation from cold air and vibration
- New style carrying case sets combining Luna impact wrenches with Teng Tools impact sockets and accessories

Impact wrenches - 3/8" drive

A choice of robust and powerful, 3/8" reversible impact wrenches especially developed for professional workshop applications. High torque action with three steps and reverse. Housing manufactured in hard wearing magnesium/aluminium. Handle exhaust. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. Stepless trigger. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration.



Stock no		205680101	205680200
Square drive	inch	3/8"	3/8"
Bolt capacity	mm	M6-M12	M6-M12
Free speed	rpm	11000	10100
Max. torque (3 steps)	Nm	160/250/300	220/365/420
Max. torque (3 steps)	ft-lb	120/187/224	164/272/314
Max. reverse torque	Nm	480	450
Max. reverse torque	ft-lb	358	336
Recommended torque range	Nm	160-250	220-380
Recommended torque range	ft-lb	119-186	164-284
Hammer mechanism	type	Pin clutch	Twin hammer
Sound level (ISO 8662-7)	dB (A)	87	90
Vibration (ISO 15744:1999)	m/s ²	2.5	2.5
Hose size	inch	3/8"	3/8"
Connection thread		1/4"	1/4"
Air consumption at 100%int*	l/min	550	550
Air consumption at 15% int*	l/min	82.5	82.5
Air consumption at 100% int*	cfm	19.42	19.42
Air consumption at 15% int*	cfm	2.9	2.9
Weight	kg	1.37	1.36
Price		€170.00	€185.00

At 6.2 bar



Impact Wrenches - 3/8" drive

A robust and powerful, composite reversible impact wrench especially developed for professional workshop applications. High torque action with dial switch for three forward speeds and two reverse speeds. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.

Stock no	150440105	
Square drive	inch	3/8"
Bolt capacity	mm	M6-M12
Free speed	rpm	9600
Max torque	Nm	460
Max torque	ft-lb	344
Max. torque (3 steps)	Nm	250/310/445
Max. torque (3 steps)	ft-lb	186/231/332
Max. reverse torque	Nm	515
Max. reverse torque	ft-lb	384
Recommended torque range	Nm	250-400
Recommended torque range	ft-lb	186-299
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	85
Vibration (ISO 15744:1999)	m/s ²	2.5
Hose size	inch	3/8"
Connection thread		1/4
Air consumption at 100%int*	l/min	900
Air consumption at 15% int*	l/min	135
Air consumption at 100% int*	cfm	31.8
Air consumption at 15% int*	cfm	4.7
Weight	kg	1.2
Price	€245.00	

At 6.2 bar



Impact Wrenches - 1/2" drive

A robust and powerful, reversible impact wrench especially developed for professional workshop applications. High torque action with three steps and reverse. Housing manufactured in hard wearing magnesium/aluminium. Handle exhaust. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. Stepless trigger. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes 9 Teng Tools impact sockets covering all the popular sizes from 10 to 21 mm and 3 deep wheel nut sockets with protective collars together with a 5" impact extension bar and universal joint and a mini oiler.

Stock no	204560056	204560106
Square drive	inch	1/2"
Impact sockets - standard	mm	10,11,13,15,16,17,18,19,21
Impact sockets - deep wheel nut	mm	17,19,21
Extension bar	inch	5
Square drive	inch	1/2"
Bolt capacity	mm	M10-M18
Free speed	rpm	8350
Max. torque (3 steps)	Nm	500/610/700
Max. torque (3 steps)	ft-lb	374/455/523
Max. reverse torque	Nm	720
Max. reverse torque	ft-lb	538
Recommended torque range	Nm	500-650
Recommended torque range	ft-lb	374-486
Hammer mechanism	type	Pin Clutch Twin hammer
Sound level (ISO 8662-7)	dB (A)	85.1
Vibration (ISO 15744:1999)	m/s ²	<2.5
Hose size	inch	3/8"
Connection thread		1/4
Air consumption at 100%int*	l/min	887
Air consumption at 15% int*	l/min	133
Air consumption at 100% int*	cfm	31.3
Air consumption at 15% int*	cfm	4.7
Weight	kg	5.8
Price	€220.00	€275.00

At 6.2 bar





Impact wrenches

Impact Wrenches - 1/2" drive

A choice of robust and powerful, 1/2" reversible impact wrenches especially developed for professional workshop applications. High torque action with three steps and reverse. Housing manufactured in hard wearing magnesium/aluminium. Handle exhaust. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. Stepless trigger. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration.



Stock no		150450104	150450203
Square drive	inch	1/2	1/2
Bolt capacity	mm	M10-M18	M10-M18
Free speed	rpm	8350	7330
Max torque	Nm	500/610/700	500/610/700
Max torque	ft-lb	374/455/523	374/455/523
Max. torque (3 steps)	Nm	720	720
Max. torque (3 steps)	ft-lb	538	538
Max. reverse torque	Nm	500-600	500-600
Max. reverse torque	ft-lb	374-486	374-486
Hammer mechanism	type	Pin Clutch	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	85.1	88.0
Vibration (ISO 15744:1999)	m/s ²	<2.5	<2.5
Hose size	inch	3/8	3/8
Connection thread		1/4	1/4
Air consumption at 100%int*	l/min	887	887
Air consumption at 15% int*	l/min	133	133
Air consumption at 100% int*	cfm	31.3	31.3
Air consumption at 15% int*	cfm	4.7	4.7
Weight	kg	2.41	2.43
Price		€149.90	€199.90

At 6.2 bar

Impact Wrenches - 1/2" drive

A sound absorbent, low weight composite reversible impact wrench especially developed for professional workshop applications. High torque action with dial switch for three forward speeds and two reverse speeds. Handle exhaust 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes 9 Teng Tools impact sockets covering all the popular sizes from 10 to 21 mm and 3 deep wheel nut sockets with protective collars together with a 5" impact extension bar, universal joint and a mini oiler.



Stock no		207500109
Square drive	inch	1/2"
Impact sockets - standard	mm	10, 11, 13, 15, 16, 17, 18, 19, 21
Impact sockets - deep wheel nut	mm	17, 19, 21
Extension bar	inch	5
Bolt capacity	mm	M8-M16
Free speed	rpm	8500
Max torque	Nm	690
Max torque	ft-lb	515
Max. torque (3 steps)	Nm	490/585/690
Max. torque (3 steps)	ft-lb	366/437/515
Max. reverse torque	Nm	720
Max. reverse torque	ft-lb	538
Recommended torque range	type	490-600
Recommended torque range	dB (A)	366-448
Hammer mechanism	m/s ²	Twin Hammer
Sound level (ISO 8662-7)	inch	85.5
Vibration (ISO 15744:1999)		2.5
Hose size	l/min	3/8"
Connection thread	l/min	1/4"
Air consumption at 100%int*	cfm	1360
Air consumption at 15% int*	cfm	204
Air consumption at 100% int*	cfm	51.5
Air consumption at 15% int*	cfm	7.7
Weight	kg	5.3
Price		€295.00

At 6.2 bar



Impact wrenches - 1/2" drive mini lightweight model

A robust and powerful, composite reversible impact wrench especially developed for professional workshop applications. High torque action with dial switch for three forward speeds and two reverse speeds. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.

Stock no		207340100
Square drive	inch	1/2"
Bolt capacity	mm	M6-M12
Free speed	rpm	10000
Max torque	Nm	530
Max torque	ft-lb	396
Max. torque (3 steps)	Nm	280/370/475
Max. torque (3 steps)	ft-lb	209/276/355
Max. reverse torque	Nm	565
Max. reverse torque	ft-lb	422
Recommended torque range	Nm	280-400
Recommended torque range	ft-lb	209-299
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	85
Vibration (ISO 15744:1999)	m/s ²	2.5
Hose size	inch	3/8"
Connection thread		1/4"
Air consumption at 100%int*	l/min	930
Air consumption at 15% int*	l/min	139
Air consumption at 100% int*	cfm	35.2
Air consumption at 15% int*	cfm	5.3
Weight	kg	1.2
Price		€215.00

At 6.2 bar



Impact Wrenches - 1/2" drive

A robust and powerful, composite reversible impact wrench especially developed for professional workshop applications. High torque action with dial switch for three forward speeds and two reverse speeds. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.

Stock no		207340209
Square drive	inch	1/2"
Bolt capacity	mm	M8-M16
Free speed	rpm	8500
Max torque	Nm	690
Max torque	ft-lb	515
Max. torque (3 steps)	Nm	490/585/690
Max. torque (3 steps)	ft-lb	366/437/515
Max. reverse torque	Nm	720
Max. reverse torque	ft-lb	538
Recommended torque range	Nm	490-600
Recommended torque range	ft-lb	366-448
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	85.5
Vibration (ISO 15744:1999)	m/s ²	2.5
Hose size	inch	3/8"
Connection thread		1/4"
Air consumption at 100%int*	l/min	1360
Air consumption at 15% int*	l/min	204
Air consumption at 100% int*	cfm	51.5
Air consumption at 15% int*	cfm	7.7
Weight	kg	1.91
Price		€240.00

At 6.2 bar





Impact wrenches

Impact wrenches - 3/4" drive

A robust and powerful, reversible impact wrench especially developed for professional workshop applications. High torque action with three steps and reverse. Housing manufactured in hard wearing magnesium/aluminium.

Handle exhaust. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. Stepless trigger. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration. 3/4" drive gun has a retaining ring for impact sockets.



Stock no		205690100
Square drive	inch	3/4"
Bolt capacity	mm	M18-M27
Free speed	rpm	5500
Max. torque (3 steps)	Nm	1080/1390/1560
Max. torque (3 steps)	ft-lb	805/1040/1165
Max. reverse torque	Nm	1560
Max. reverse torque	ft-lb	1165
Recommended torque range	Nm	750-1200
Recommended torque range	ft-lb	560-900
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	89.6
Vibration (ISO 15744:1999)	m/s ²	2.16
Hose size	inch	1/2"
Connection thread		3/8"
Air consumption at 100%int*	l/min	1400
Air consumption at 15% int*	l/min	210
Air consumption at 100% int*	cfm	49.4
Air consumption at 15% int*	cfm	7.4
Weight	kg	5.22
Price		€395.00

Support handle	205691009
Price	€42.00

At 6.2 bar

Impact Wrenches - 3/4" drive

A sound absorbent, lightweight composite reversible impact wrench especially developed for professional workshop applications. High torque action with dial switch for three forward speeds and two reverse speeds. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.



Stock no		207930108
Square drive	inch	3/4"
Bolt capacity	mm	M18-M27
Free speed	rpm	5750
Max torque	Nm	1626
Max torque	ft-lb	1200
Max. torque (3 steps)	Nm	405/1010/1215
Max. torque (3 steps)	ft-lb	300/750/900
Max. reverse torque	Nm	1685
Max. reverse torque	ft-lb	1250
Recommended torque range	Nm	335-1145
Recommended torque range	ft-lb	250-850
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	89.6
Vibration (ISO 15744:1999)	m/s ²	1.71
Hose size	inch	1/2"
Connection thread		3/8"
Air consumption at 100%int*	l/min	1300
Air consumption at 15% int*	l/min	195
Air consumption at 100% int*	cfm	49.9
Air consumption at 15% int*	cfm	6.9
Weight	kg	3.15
Price		€550.00

At 6.2 bar



Impact Wrenches - 3/4" drive

A very strong and highly efficient impact wrench with twin hammer mechanism especially developed for heavy duty applications. High torque action with three forward and three reverse speeds. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Side support handle and rear handle for easy use. Housing manufactured in magnesium/aluminium with rubber protectors on each edge to protect the machine further.

Stock no	207320102	
Square drive	inch	3/4"
Bolt capacity	mm	M18-M27
Free speed	rpm	4500
Max torque	Nm	3300
Max torque	ft-lb	2450
Max. torque (3 steps)	Nm	1850/2500/2700
Max. torque (3 steps)	ft-lb	1370/1850/2000
Max. reverse torque	Nm	2000/2700/2900
Max. reverse torque	ft-lb	1480/2000/2150
Recommended torque range	Nm	500-2500
Recommended torque range	ft-lb	370-1850
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	111.4
Vibration (ISO 15744:1999)	m/s ²	3.01
Hose size	inch	3/4
Connection thread		1/2
Air consumption at 100%int*	l/min	1860
Air consumption at 15% int*	l/min	279
Air consumption at 100% int*	cfm	65.7
Air consumption at 15% int*	cfm	485
Weight	kg	9.8
Price	€1050.00	

At 6.2 bar



Impact Wrenches - 1" drive

A robust and powerful, reversible impact wrench especially developed for professional workshop applications. High torque action with three steps and reverse. Housing manufactured in hard wearing magnesium/aluminium. Handle exhaust. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. Stepless trigger. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration. The 1" drive gun has a retaining hole/pin system for the impact sockets.

Stock No	205690209	
Square drive	inch	1"
Bolt capacity	mm	M22-M33
Free speed	rpm	5500
Max. torque (3 steps)	Nm	1080/1390/1560
Max. torque (3 steps)	ft-lb	805/1040/1165
Max. reverse torque	Nm	1560
Max. reverse torque	ft-lb	1165
Recommended torque range	Nm	750-1200
Recommended torque range	ft-lb	560-900
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	89.6
Vibration (ISO 15744:1999)	m/s ²	<2.16
Hose size	inch	1/2"
Connection thread		3/8"
Air consumption at 100%int*	l/min	1400
Air consumption at 15% int*	l/min	210
Air consumption at 100% int*	cfm	49.4
Air consumption at 15% int*	cfm	7.4
Weight	kg	5.25
Price	€410.00	

At 6.2 bar





Impact wrenches

Impact Wrenches - 1" drive

A very strong and highly efficient impact wrench with twin hammer mechanism especially developed for heavy duty applications. High torque action with three forward and three reverse speeds. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Side support handle and rear handle for easy use. Housing manufactured in magnesium/aluminium with rubber protectors on each edge to protect the machine further.



Stock No	207320201	
Square Drive	inch	1"
Bolt capacity	mm	M22-M33
Free speed	rpm	4500
Max torque	Nm	3300
Max torque	ft-lb	2450
Max. torque (3 steps)	Nm	1850/2500/2700
Max. torque (3 steps)	ft-lb	1370/1850/2000
Max. reverse torque (3 steps)	Nm	2000/2700/2900
Max. reverse torque (3 steps)	ft-lb	1480/2000/2150
Recommended torque range	Nm	600-2700
Recommended torque range	ft-lb	445-2000
Hammer mechanism	type	Twin Hammer
Sound level (ISO 8662-7)	dB (A)	111.4
Vibration (ISO 15744:1999)	m/s ²	<3.01
Hose size	inch	3/4
Air inlet	inch	1/2"
Air consumption at 100% int*	l/min	1860
Air consumption at 15%int*	l/min	279
Air consumption at 100% int*	cfm	65.7
Length of machine	mm	485
Weight of machine	kg	9.9
Price		€1050.00

At 6.2 bar

Air Ratchets

A robust and powerful, reversible air ratchet wrench especially developed for professional workshop applications. Produced from high quality steel with a rolling forged pawl mechanism. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. The 3/8" set is supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet, including 9 impact sockets, extension bar, an adaptor from 3/8" - 1/2", a mini oiler and 10ml of air tool oil. The 1/2" set is supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet, including Teng Tools impact sockets, extension bars, universal joint (1/2" drive set only), mini oiler and 10ml of air tool oil. Both have a ball type square drive for the impact sockets.



Stock no	205730104		205730203	
Square drive	inch	3/8	1/2	
Impact sockets - regular	mm	8, 10, 12, 13, 14, 16, 17, 19	10, 11, 12, 13, 15, 17, 19	
Impact sockets - deep	mm	8, 10, 12, 13, 14, 16, 17, 19	10, 11, 12, 13, 15, 17, 19	
Extension bars	inch	3"	3" & 5"	
Adaptor	pcs	3/8"F:1/4"M & 3/8"F:1/2"M	1/2"F:3/8"M	
Bolt capacity	mm	M5-M8	M6-M10	
Free speed	rpm	240	240	
Max. torque	Nm	120	120	
Max. torque	ft-lb	90	90	
Recommended torque range	Nm	15-100	15-100	
Recommended torque range	ft-lb	11.2-75	11.2-75	
Sound level (ISO 8662-7)	dB (A)	92	92	
Vibration (ISO 15744:1999)	m/s ²	<3.5	<3.5	
Min. hose size	inch	3/16	3/16	
Air Inlet	inch	1/4	1/4	
Air consumption at 100% int*	l/min	755	755	
Air consumption at 15% int*	l/min	113	113	
Air consumption at 100% int*	cfm	26.6	26.6	
Air consumption at 15% int*	cfm	4.0	4.0	
Length	mm	330	330	
Weight	kg	3.3	3.3	
Price		€215.00	€230.00	

At 6.2 bar



Luna Air Ratchets

Robust and powerful air ratchet wrenches especially developed for professional workshop applications and featuring –

- Produced from high quality steel with a rolling forged pawl mechanism
- Ergonomically designed rubber handle for a better grip and insulation from cold air and vibration
- Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose
- New style trigger for more comfortable use
- New style carrying case sets combining Luna impact wrenches with Teng Tools impact sockets and accessories

Air Ratchets

A robust powerful air ratchet wrench especially designed for professional workshop applications. Produced from high quality steel with a rolling forged pawl mechanism. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration. 360° swivelling air outlet to direct the air away from the user.

Stock no		205720105	205720204
Square drive	inch	¾	½
Bolt capacity	mm	M5-M8	M6-M10
Free speed	rpm	240	240
Max. torque	Nm	120	120
Max. torque	ft-lb	90	90
Recommended torque range	Nm	15-100	15-100
Recommended torque range	ft-lb	11.2-75	11.2-75
Sound level (ISO 8662-7)	dB (A)	92	92
Vibration (ISO 15744:1999)	m/s ²	<3.5	<3.5
Min. hose size	inch	¾	¾
Air Inlet	inch	¼	¼
Air consumption at 100% int*	l/min	755	755
Air consumption at 15% int*	l/min	113	113
Air consumption at 100% int*	cfm	26.6	26.6
Air consumption at 15% int*	cfm	4.0	4.0
Length	mm	330	330
Weight	kg	1.35	1.35
Price		€125.00	€125.00

At 6.2 bar



Air Ratchets - Stubby

A robust powerful air ratchet wrench especially designed for professional workshop applications. Produced from high quality steel with a rolling forged pawl mechanism. Ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air hose. The ¾" model has a built in quick release function for the sockets.

Stock no		207330101	207330200
Square drive	inch	¾	¾
Bolt capacity	mm	M10	M10
Free speed	rpm	280	280
Max. torque	Nm	34	34
Max. torque	ft-lb	25.2	25.2
Recommended torque range	Nm	8-34	8-34
Recommended torque range	ft-lb	5.9-25.2	5.9-25.2
Sound level (ISO 8662-7)	dB (A)	89.1	87.5
Vibration (ISO 15744:1999)	m/s ²	<2.32	<2.97
Min. hose size	inch	¾	¾
Air Inlet	inch	¼	¼
Air consumption at 100% int*	l/min	420	420
Air consumption at 15% int*	l/min	63	63
Air consumption at 100% int*	cfm	2.0	2.0
Air consumption at 15% int*	cfm	0.3	0.3
Length	mm	165	165
Weight	kg	0.53	0.53
Price		€135.00	€135.00

At 6.2 bar





Air Screwdrivers

Air Screwdrivers

A professional quality reversible air screwdriver for 1/4" hex bits with variable speed trigger, forward/reverse control, ergonomically designed comfortable grip and handle exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Supplied with 3 different torque springs to suit individual applications. Features include a quick release bit holder and an adjustable clutch mechanism on tightening and full power without clutch for loosening to remove even the most stubborn fastenings. The machine has an automatic start when the bit is pressed to the fastening and the trigger pulled.



Stock no	207750100	
Drive	hexagon	1/4
Screw capacity	mm	6
Free speed	rpm	800
Torque	Nm	1.1-14.6
Sound level (ISO 8662-7)	dB (A)	82
Vibration (ISO 15744:1999)	m/s ²	<0.7
Hose size	inch	3/8
Connection thread		1/4
Air consumption at 100% int*	l/min	555
Air consumption at 20% int*	l/min	111
Air consumption at 100% int*	cfm	19.6
Air consumption at 20% int*	cfm	3.9
Weight	kg	0.95
Price	€185.00	

At 6.2 bar

A professional quality reversible straight model reversible air screwdriver for 1/4" hex bits, reversible, ergonomically designed comfortable grip with handle exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Supplied with three different torque springs to suit individual applications. Features include a hanging ring and adjustable clutch mechanism. The machine has an automatic start when the bit is pressed to the fastening.



Stock no	200280105	
Drive	hexagon	1/4
Screw capacity	mm	6
Free speed	rpm	1100
Torque	Nm	0.4-4.5
Sound level (ISO 8662-7)	dB (A)	84
Vibration (ISO 15744:1999)	m/s ²	0.5
Hose size	inch	3/8
Connection thread		1/4
Air consumption at 100% int*	l/min	565
Air consumption at 20% int*	l/min	113
Air consumption at 100% int*	cfm	20.0
Air consumption at 20% int*	cfm	4.0
Weight	kg	0.7
Price	€440.00	

At 6.2 bar

Air Drills

A professional quality 3/8" drive reversible air drill ergonomically designed comfortable grip and rear exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The sets offer a choice of key chuck or quick chucks and each includes a 19 piece drill bit set covering 1 to 10mm in 0.5mm steps, a mini oiler, a Teng Tools centre punch and a side support handle for left or right handed use. Spare key (3/8") order part number 126391002.



Stock No		208060103	208060202
Chuck size	inch	3/8	3/8
Chuck size	mm	10	10
Free speed	rpm	1800	1800
Chuck type		Key chuck	Quick chuck
Spindle thread	UNF	3/8x24	3/8x24
Sound level (ISO 8662-7)	dB (A)	82	82
Vibration (ISO 15744:1999)	m/s ²	0.8	0.8
Min. hose size	inch	3/8	3/8
Connection thread	G (R)	1/4	1/4
Air consumption at 100% int*	l/min	550	550
Air consumption at 20% int*	l/min	110	110
Air consumption at 100% int*	cfm	19.42	19.42
Air consumption at 20% int*	cfm	3.88	3.88
Weight	kg	1.3	1.4
Mini oiler	square drive	1/4	1/4
Drill bits	mm	1-10	1-10
Accessories		side handle, centre punch	side handle, centre punch
Price		€250.00	€260.00

All prices exclude VAT and are subject to availability



Air Drills

A professional workshop quality 1/4" chuck air drill with variable speed trigger, ergonomically designed comfortable grip and rear exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line.

Stock no	206380107	
Chuck size	inch	1/4
Free speed	rpm	2800
Spindle thread	UNF	3/8x24
Chuck type	Key chuck	
Air inlet	inch	1/4
Hose size	inch	3/8
Air pressure	psi	90
Air consumption at 100% int*	l/min	420
Air consumption atr 20% int*	l/min	84
Air consumption at 100% int*	l/s	7.0
Air consumption atr 20% int*	cfm	2.97
Sound level (CEN/TC 255 N81)	dB(A)	84
Vibration (ISO 5349)	m/s ²	0.4
Length	mm	140
Weight	kg	0.6
Price	€255.00	
Spare key for 1/4" chuck	206381006	
Price	€2.60	

At 6.2 bar



A professional workshop quality 3/8" chuck reversible air drill with variable speed trigger, forward/reverse control, ergonomically designed comfortable grip and rear exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line.

Stock no	206390106	206390205	
Chuck size	inch	3/8	3/8
Free speed	rpm	1800	1800
Spindle thread	UNF	3/8x24	3/8x24
Chuck Type		Key Chuck	Quick Chuck
Air inlet	inch	1/4	1/4
Hose size	inch	3/8	3/8
Air pressure	psi	90	90
Air consumption at 100% int*	l/min	550	550
Air consumption at 20% int*	l/min	110	110
Air consumption at 100% int*	cfm	19.42	19.42
Air consumption at 20% int*	cfm	3.88	3.88
Sound level (CEN/TV 255 N81)	dB (A)	82	82
Vibration (ISO 5349)	m/s ²	0.8	0.8
Length	mm	186	186
Weight	kg	1.3	1.4
Price	€155.00	€165.00	
Spare key for 3/8" chuck	200830206		
Price	€1.20		
Support handle	206401002		
Price	€22.90		

At 6.2 bar





Air drills

Air Drills

A professional workshop quality 1/2" chuck reversible air drill with variable speed trigger, forward/reverse control, ergonomically designed comfortable grip and rear exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Includes a side support handle for left or right handed use.



Quick chuck

Key chuck

Stock no		206400103	206400202
Chuck size	inch	1/2	1/2
Free speed	rpm	800	800
Spindle thread		3/8x24	3/8x24
Chuck type		Key chuck	Quick chuck
Air inlet	inch	1/4	1/4
Hose size	inch	3/8	3/8
Air pressure	psi	90	90
Air consumption at 100% int*	l/min	635	635
Air consumption at 20% int*	l/min	127	127
Air consumption at 100% int*	cfm	22.43	22.43
Air consumption at 20% int*	cfm	4.49	4.49
Sound level (CEN/TC 255 N81)	dB (A)	79	79
Vibration (ISO 5349)	m/s ²	0.7	0.7
Length	mm	212	212
Weight	kg	1.6	1.7
Price		€225.00	€225.00
Spare key for 1/2" chuck		206391005	
Prices		€3.20	
Support handle		206401002	
Price		€22.90	

At 6.2 bar

A professional quality 3/8" drive straight handle air drill with twist grip speed regulator, ergonomically designed comfortable grip and handle exhaust for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Supplied with support handle.



Stock no		208100107
Chuck size	inch	3/8
Chuck type		Key chuck
Spindle thread		UNF
Free speed	rpm	1800
Air inlet	inch	1/4
Hose size	inch	3/8
Air consumption at 100% int*	l/min	550
Air consumption at 20% int*	l/min	110
Air consumption at 100% int*	cfm	19.42
Air consumption at 20% int*	cfm	3.88
Sound level (CEN/TC 255 N81)	dB (A)	82
Vibration (ISO 5349)	m/s ²	0.8
Weight	kg	1.3
Price		€199.00
Spare key for 3/8" chuck		200830206
Price		€1.20
Support handle		208100503
Price		€32.90

At 6.2 bar



Angle grinders

A professional quality angle grinder for 4 1/2" or 5" grinding and cut off discs. Features include a safety lever to prevent unwanted starting, an anti vibration support handle and a disc guard with 9 individual, adjustable positions. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. A quick release hand operated flange to facilitate easy change over of grinding discs is available as an option (order item number 207770504 as below).

Stock no		207770108	207770207
For grinding disc	mm	115x22	125x22
Spindle thread		M14	M14
Free speed	rpm	10000	10000
Sound level (CEN/TC 255 N81)	dB (A)	82	82
Vibration (ISO 5349)	m/s ²	2.4	2.4
Min. hose size	inch	3/8	3/8
Air inlet		1/4	1/4
Air consumption at 100% int*	l/min	450	450
Air consumption at 50% int*	l/min	225	225
Air consumption at 100% int*	cfm	15.9	15.9
Air consumption at 50% int*	cfm	7.9	7.9
Power	W	485	485
Weight	kg	1.9	1.9
Price		€335.00	€335.00
Hand operated flange (M14)		207770504	
Price		€33.10	

At 6.2 bar



Die Grinders

A mini die grinder set designed for rotary files and mounted stones. A high speed performance suitable for accessories with shaft diameters of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with stepless twist grip speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a safety lever to prevent unwanted starting and rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes five 3mm mounted stones, five 6mm mounted stones, a mini oiler, adaptor sleeves and two adjustment spacers.

Stock no		207390105
For shaft diameter		3mm, 6mm, 1/4"
Free speed	rpm	25000
Sound level (ISO 8662-7)	dB (A)	83
Vibration (ISO 15744:1999)	m/s ²	3.6
Min. hose size	inch	3/8
Air inlet		1/4
Air consumption at 100% int*	l/min	330
Air consumption at 40% int*	l/min	132
Air consumption at 100% int*	cfm	11.7
Air consumption at 40% int*	cfm	4.7
Power	W	224
Weight	kg	1.0
Price		€110.00
**3mm Adaptor sleeve		207360504
Price		€5.80
**6mm Adaptor sleeve		207360603
Price		€5.80
**1/4" Adaptor sleeve		207360702
Price		€5.80

At 6.2 bar





Grinding & Finishing tools

Die Grinders - Mini

A mini die grinder designed for rotary files and mounted stones. A high speed performance suitable for accessories with shaft diameters of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with stepless twist grip speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a safety lever to prevent unwanted starting and rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.



Stock no	207370107	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	25000
Sound level (ISO 8662-7)	dB (A)	83
Vibration (ISO 15744:1999)	m/s ²	3.6
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	330
Air consumption at 40% int*	l/min	132
Air consumption at 100% int*	cfm	11.7
Air consumption at 40% int*	cfm	4.7
Length	mm	160
Power	W	224
Weight	kg	0.4
Price	€85.90	
3mm Adaptor Sleeve	207360504	
Price	€5.80	
6mm Adaptor Sleeve	207360603	
Price	€5.80	
1/4" Adaptor Sleeve	207360702	
Price	€5.80	

At 6.2 bar

Die Grinders - Midi

A midi die grinder designed for rotary files and mounted stones. A high speed performance suitable for accessories with shaft diameters of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with stepless twist grip speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a safety lever to prevent unwanted starting and rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.



Stock no	207360108	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	22000
Sound level (ISO 8662-7)	dB (A)	91
Vibration (ISO 15744:1999)	m/s ²	<2.5
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	550
Air consumption at 40% int*	l/min	220
Air consumption at 100% int*	cfm	19.4
Air consumption at 40% int*	cfm	7.8
Length	mm	165
Power	W	373
Weight	kg	0.65
Price	€139.10	
3mm adaptor sleeve	207360504	
Price	€5.80	
6mm adaptor sleeve	207360603	
Price	€5.80	
1/4" adaptor sleeve	207360702	
Price	€5.80	

At 6.2 bar



Die Grinders - Long reach

A long reach die grinder designed for rotary files and mounted stones. A high speed performance suitable for accessories with shaft diameters of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with stepless twist grip speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a safety lever to prevent unwanted starting and rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.

Stock no.	207420100	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	25000
Sound level (ISO 8662-7)	m	88
Vibration (ISO 15744:1999)	m/s ²	3.6
Min. hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	330
Air consumption at 40% int*	l/min	132
Air consumption at 100% int*	cfm	11.7
Air consumption at 40% int*	cfm	4.7
Length	mm	255
Power	W	224
Weight	kg	0.7
Price	€146.00	
3mm adaptor sleeve	207360504	
Price	€5.80	
6mm adaptor sleeve	207360603	
Price	€5.80	
1/4" adaptor sleeve	207360702	
Price	€5.80	

At 6.2 bar



Die Grinders - Straight

A high power straight die grinder for rotary files and mounted stones. A very strong machine for tough applications. For accessories with a shaft diameter of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with rear exhaust, safety lever to prevent unwanted starts, built in speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Designed for easy use with an ergonomic grip which insulates against cold air and vibration.

Stock no.	200260107	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	20000
Sound level (ISO 8662-7)	m	85
Vibration (ISO 15744:1999)	m/s ²	1.2
Min. hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	320
Air consumption at 40% int*	l/min	128
Air consumption at 100% int*	cfm	11.3
Air consumption at 40% int*	cfm	4.5
Length	mm	208
Power	W	750
Weight	kg	1.0
Price	€165.00	
3mm adaptor sleeve	200260503	
Price	€7.40	
6mm adaptor sleeve	200260602	
Price	€7.40	
1/4" adaptor sleeve	200260701	
Price	€7.40	

At 6.2 bar





Die Grinders - 90° angled mini

A 90° angled mini die grinder designed for rotary files and mounted stones. A high speed performance suitable for accessories with shaft diameters of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with stepless twist grip speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a safety lever to prevent unwanted starting and rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.



Stock no	207380106	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	20000
Sound level (ISO 8662-7)	dB (A)	93
Vibration (ISO 15744:1999)	m/s ²	<2.5
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	330
Air consumption at 40% int*	l/min	132
Air consumption at 100% int*	cfm	11.7
Air consumption at 40% int*	cfm	4.7
Length	mm	165
Power	W	224
Weight	kg	0.5
Price	€139.10	
3mm adaptor sleeve	207360504	
Price	€5.80	
6mm adaptor sleeve	207360603	
Price	€5.80	
1/4" adaptor sleeve	207360702	
Price	€5.80	

At 6.2 bar

Die Grinders - 90° angled

A high power 90° angled die grinder for rotary files and mounted stones. A very strong machine for tough applications. For accessories with a shaft diameter of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with rear exhaust, safety lever to prevent unwanted starts, built in speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Designed for easy use with an ergonomic grip which insulates against cold air and vibration.



Stock no	200270106	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	12000
Sound level (ISO 8662-7)	dB (A)	89
Vibration (ISO 15744:1999)	m/s ²	1.7
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	320
Air consumption at 40% int*	l/min	128
Air consumption at 100% int*	cfm	11.3
Air consumption at 40% int*	cfm	4.5
Length	mm	232
Power	W	750
Weight	kg	1.0
Price	€199.00	
3mm adaptor sleeve	200260503	
Price	€7.40	
6mm adaptor sleeve	200260602	
Price	€7.40	
1/4" adaptor sleeve	200260701	
Price	€7.40	

At 6.2 bar



Die Grinders - 115° angled mini

A 115° angled mini die grinder designed for rotary files and mounted stones. A high speed performance suitable for accessories with shaft diameters of 3mm, 6mm or 1/4" (adaptor sleeves included). Equipped with stepless twist grip speed regulator and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a safety lever to prevent unwanted starting, rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration.

Stock no	207410101	
For shaft diameter	3mm, 6mm, 1/4"	
Free speed	rpm	20000
Sound level (ISO 8662-7)	dB (A)	93
Vibration (ISO 15744:1999)	m/s ²	<2.5
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	330
Air consumption at 40% int*	l/min	132
Air consumption at 100% int*	cfm	11.7
Air consumption at 40% int*	cfm	4.7
Length	mm	165
Power	W	224
Weight	kg	0.5
Price	€149.30	
3mm adaptor sleeve	207360504	
Price	€5.80	
6mm adaptor sleeve	207360603	
Price	€5.80	
1/4" adaptor sleeve	207360702	
Price	€5.80	

At 6.2 bar



Micro Die Grinders

Micro die grinders designed for rotary files and mounted stones with 3mm shaft diameters and a choice of high speed performance levels. Features include an adjustable stepless variable speed. Supplied with a 3mm adaptor sleeve, a 0.4m air drain hose and a 1.5 metre assembled air line with a 360° swivelling air intake to make the machine easier to use with little interference from the air line.

Stock no		207400102	207400201
For shaft diameter		3	3
Free speed	rpm	54000	70000
Sound level (ISO 8662-7)	dB (A)	78	81
Vibration (ISO 15744:1999)	m/s ²	2.0	2.0
Hose size	inch	3/16	3/16
Air inlet	inch	1/4	1/4
Air consumption at 100% int*	l/min	160	160
Air consumption at 40% int*	l/min	64	64
Air consumption at 100% int*	cfm	5.6	5.6
Air consumption at 40% int*	cfm	2.2	2.2
Length	mm	137	137
Weight	kg	0.2	0.2
Price		€112.50	€137.80
3mm adaptor sleeve		207400508	
Price		€7.10	

At 6.2 bar





Grinding & Finishing tools

Jitterbug Sanders

Efficient and easy to operate machines with oscillating movement for use with abrasive paper with velcro type fastening. Developed for professional workshop applications and featuring one handed grip, low weight, low vibration, rear exhaust, and 360° swivelling air intake to make the machine easier to use with little interference from the air line, stepless speed regulator, ergonomic, non slip composite housing and recessed lever for more comfortable use. Three models are available giving a choice of non vacuum, self generated vacuum (with hose and dust bag) or central vacuum.



Stock no	202480109	202480208	202480307
Type	non vacuum	self generating vacuum	central vacuum
Grinding pad dimension	mm 130 x 80	130 x 80	130 x 80
Suitable abrasive paper	mm 130 x 80	130 x 80	130 x 80
Free speed	rpm 10000	10000	10000
Orbital diameter	mm 2.5	2.5	2.5
Sound level (ISO 8662-7)	dB (A) 78	78	78
Vibration (ISO 15744:1999)	m/s ² 3.0	3.0	3.0
Hose size	inch 3/8	3/8	3/8
Air inlet	inch 1/4	1/4	1/4
Air consumption at 100% int*	l/min 510	510	510
Air consumption at 40% int*	l/min 255	255	255
Air consumption at 100% int*	cfm 18.0	18.0	18.0
Air consumption at 40% int*	cfm 9.0	9.0	9.0
Dimensions (L x W x H)	mm 168 x 80 x 92	168 x 80 x 92	168 x 80 x 92
Weight	kg 0.68	0.72	0.73
Price	€265.00	€275.00	€270.00
Grinding Pad (130 x 80mm)	202481008	202481107	202481107
Price	€22.60	€24.70	€24.70
Vacuum hose		207490707	
Price		€19.20	
Dust bag		207490806	
Price		€12.30	

At 6.2 bar

Random Orbital Sanders

Professional quality one hand grip random orbital sanders for use with 6" Velcro fastening grinding papers. An ergonomic non slip composite housing and rear exhaust, designed to give better grip and insulation from cold air and vibration. Features include a lever which is recessed into the handle when in use, a stepless speed regulator, lightweight and low vibration and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Three models are available giving a choice of non vacuum, self generated vacuum (with hose and dust bag) or central vacuum use. An alternative grinding pad is available or use with 6" self adhesive grinding discs.



Stock no	207490103	207490202	207490301
Type	non vacuum	self generating vacuum	central vacuum
Grinding pad diameter	inch 6	6	6
Free speed	rpm 12000	12000	12000
Spindle thread	UNF 5/16x24	5/16x24	5/16x24
Orbital diameter	mm 5	5	5
Sound level (EN ISO 15744))	dB (A) 82	82	82
Vibration (ISO 8662-8)	m/s ² <2.4	<2.4	<2.4
Hose size	inch 3/8	3/8	3/8
Air inlet	inch 1/4	1/4	1/4
Air consumption at 100% int*	l/min 300	300	300
Air consumption at 50% int*	l/min 150	150	150
Air consumption at 100% int*	cfm 10.6	10.6	10.6
Air consumption at 50% int*	cfm 5.3	5.3	5.3
Weight	kg 0.9	0.9	0.9
Price	€235.00	€245.00	€230.00
Grinding pad 6" - velcro fastening	207490509	207490509	207490509
Price	€21.70	€21.70	€21.70
Grinding pad 6" - self adhesive	207490608	207490608	207490608
Price	€19.50	€19.50	€19.50
Vacuum hose 1.75m	207490707	207490707	207490707
Price	€19.20	€19.20	€19.20
Dust bag	207490806	207490806	207490806
Price	€12.30	€12.30	€12.30

At 6.2 bar



Belt Sanders

Professional quality belt sanders for use with sanding belts for wood, metal or plastic. A 360° adjustable handle makes the machine suitable for grinding in narrow spaces, on internal surfaces and in corners. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a spark deflector, a safety lever to prevent unwanted starting and a 360° rotating exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Two models are available giving a choice of 6/10mm or 20mm contact arms for use with different width sanding belts (2 of each size sanding belt per arm included).

Stock no		207730102	207730201
For sanding belt	mm	6/10x330	20x520
Free speed	rpm	18000	16000
Sound level (CEN/TC 255 N81)	dB (A)	82	84
Vibration (ISO 5349)	m/s ²	3.1	3.1
Hose size	inch	5/16	5/16
Air inlet	inch	1/4	1/4
Air consumption at 100% int*	l/min	630	740
Air consumption at 50% int*	l/min	315	370
Air consumption at 100% int*	cfm	22.3	26.1
Air consumption at 50% int*	cfm	11.1	13.1
Length	mm	285	355
Weight	kg	0.9	1.5
Price		€295.00	€310.00

At 6.2 bar



Punch and Flanging Tools

A combined punch and flanging tool for easier joining of steel plates with just one tool. An air hydraulic system gives low noise levels and little vibration. The combination head swivels 360° for easier access and no tension on the steel plate. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. Designed for easy use with an ergonomic grip which insulates against cold air and vibration.

Stock no		200220101
Cutting capacity - steel	mm	1.2
Cutting capacity - aluminium	mm	2.0
Flange A	mm	12
Flange B	mm	5
Edge C (maximum)	mm	8
Working pressure	bar	6.2
Sound level (ISO 8662-7)	dB (A)	88.3
Vibration (ISO 15744:1999)	m/s ²	0.95
Hose size	inch	3/8
Connection thread	inch	1/4
Air consumption at 100% int*	l/stroke	0.5
Air consumption at 40% int*	l/stroke	0.2
Air consumption at 100% int*	ft ³ /stroke	0.02
Air consumption at 40% int*	ft ³ /stroke	0.01
Length	mm	260
Weight	kg	1.3
Price		€145.00

At 6.2 bar





Nibblers

A professional quality nibbler with extremely low vibration levels. Designed for easy use and comfort when in use.

Features include die adjustable in 45° increments, a safety lever to prevent unwanted starting, a rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line.

Suitable for cutting materials such as sheet metal and aluminium.



Stock no		207350109
Cutting width	mm	4.5
Strokes	per minute	2500
Cutting capacity - steel	mm	1.6
Cutting capacity - aluminium	mm	1.6
Sound level (PN8NTC1)	dB (A)	90
Vibration (ISO 8662)	m/s ²	4.3
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	690
Air consumption at 40% int*	l/min	276
Air consumption at 100% int*	cfm	24.4
Air consumption at 40% int*	cfm	9.7
Length	mm	200
Weight	kg	0.95
Price		€134.00
Die		207350406
Price		€12.30
Punch		207350505
Price		€8.80

At 6.2 bar

Cut Off Tools

A professional quality cut off tool for use with 3" (80mm) cut off discs. Designed for easy use and comfort when in use. Features include a disc guard, a stepless twist grip speed regulator, a safety lever to prevent unwanted starting, a rear exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Equipped with a 360° swivelling air intake to make the machine easier to use with little

interference from the air line.



Stock no		207780107
For cut off discs	mm	80x2x10
Spindle thread	UNC	3/8"x24
Free Speed	rpm	20000
Sound level (CEN/TC 255 N81)	dB (A)	85
Vibration (ISO 5349)	m/s ²	1.6
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	432
Air consumption at 40% int*	l/min	173
Air consumption at 100% int*	cfm	15.3
Air consumption at 40% int*	cfm	6.1
Weight	kg	0.9
Price		€135.00

At 6.2 bar



Reversible Cut Off Tools

A professional quality, reversible cut off tool for use with 3" (80mm) cut off discs. Designed for easy use and comfort when in use. Features include a disc guard, speed regulator, a safety lever to prevent unwanted starting, handle exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. The reversible action makes the machine suitable for left or right handed users and for directing sparks away from the operator.

Stock no		200290104
For cut off discs	mm	80x2x10
Spindle thread	UNC	3/8"x24
Free Speed	rpm	16000
Working pressure	bar	6.2
Sound level (CEN/TC 255 N81)	dB (A)	98
Vibration (ISO 5349)	m/s ²	0.5
Hose size	inch	3/8
Air inlet		1/4
Air consumption at 100% int*	l/min	432
Air consumption at 40% int*	l/min	173
Air consumption at 100% int*	cfm	15.3
Air consumption at 40% int*	cfm	6.1
Weight	kg	0.9
Price		€185.00

At 6.2 bar



Air saws

A professional quality rigid low speed machine for rough sawing. Suitable for sawing material like steel plate, aluminium, copper, plastic, wood etc. Features include an air outlet through the handle, exhaust hose that reduces the noise and leads the cool air away from the body, an adjustable saw blade support, adjustable speed regulator, also suitable for shortened hacksaw blades. Equipped with a safety lever and swivelling air inlet and supplied with 3 different hacksaw blades - 18 teeth, 24 teeth and 32 teeth.

Stock no		208690107
Stroke length	mm	10
Strokes	rpm	5000
Cutting capacity - steel	mm	3
Cutting capacity - aluminium	mm	4
Cutting capacity - wood	mm	5
Sound level (PNEUROP PN8NTC1)	dB (A)	91
Vibration (ISO 5439)	m/s ²	6.6
Hose size	inch	5/16
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	280
Air consumption at 40% int*	l/min	112
Air consumption at 100% int*	cfm	9.9
Air consumption at 40% int*	cfm	4
Length	mm	230
Weight	kg	0.96
Price		€175.00
Metal saw blade 18 teeth	5 pieces	208690404
Price		€17.50
Metal saw blade 24 teeth	5 pieces	208690503
Price		€17.50
Metal saw blade 32 teeth	5 pieces	208690602
Price		€17.50

At 6.2 bar





Micro air saws

A professional quality, versatile and easy to handle machine for many purposes. Suitable for sawing material like steel plate, aluminium, copper, plastic, wood etc. Features include an air outlet through the handle, an exhaust hose that reduces the noise and leads the cool air away from the body, an adjustable saw blade support, adjustable speed regulator, also suitable for shortened hacksaw blades. Equipped with a safety lever and swivelling air inlet and is supplied as standard with 3 different hacksaw blades - 18 teeth, 24 teeth and 32 teeth.



Stock no		208680108
Stroke length	mm	5
Strokes	rpm	7500
Cutting capacity - steel	mm	2.0
Cutting capacity - aluminium	mm	3.4
Cutting capacity - wood	mm	4.0
Sound level (PNEUROP PN8NTC1)	dB (A)	91
Vibration (ISO 5439)	m/s ²	6.6
Hose size	inch	5/16
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	170
Air consumption at 40% int*	l/min	68
Air consumption at 100% int*	cfm	6.0
Air consumption at 40% int*	cfm	2.4
Length	mm	175
Weight	kg	0.44
Price		€170.00
Metal saw blade 18 teeth	5 pieces	208690404
Price		€17.50
Metal saw blade 24 teeth	5 pieces	208690503
Price		€17.50
Metal saw blade 32 teeth	5 pieces	208690602
Price		€17.50

At 6.2 bar

Air Shears

A professional quality pistol style air shear for cutting sheet steel and aluminium. Features include a 360° adjustable cutting head, a variable speed trigger, a handle exhaust and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Equipped with a 360° swivelling air intake to make the machine easier to use with little interference from the air line.



Stock no		207760109
Cutting capacity - steel	mm	1.2
Cutting capacity - aluminium	mm	1.6
Sound level (CEN/TC 255 N81)	dB (A)	82
Vibration (ISO 5349)	m/s ²	1.1
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	383
Air consumption at 40% int*	l/min	153
Air consumption at 100% int*	cfm	13.5
Air consumption at 40% int*	cfm	5.4
Weight	mm	0.95
Price		€175.00
Extra cutting head		207760505
Price		€56.10

At 6.2 bar



Air Chisel Hammer

A professional quality pistol style air chisel hammer set for use with both hexagon and round shaft chisels. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Features include a patented shock reduction system to give low vibration and a dry shot prevention mechanism to avoid use unless the chisel is engaged. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes 4 hexagon shaft chisels, 5 round shaft chisels, a quick chuck, a spring type chuck and a mini oiler.

Stock no		208070102
Chisel holder	mm	10.2
Blows*	per minute	2900-3100
Piston stroke	mm	67
Sound level (BS EN 15744)	dB (A)	102.8
Vibration (ISO 8661-9)	m/s ²	4.98
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	636
Air consumption at 20% int*	l/min	127
Air consumption at 100% int*	cfm	24.1
Air consumption at 20% int*	cfm	4.8
Weight	kg	6.2
Price		€199.00

At 6.2 bar



Air Chisel Hammers

A professional quality pistol style air chisel hammer set for use with both hexagon and round shaft chisels. Handle exhaust and 360° swivelling air intake to make the machine easier to use with little interference from the air line. Stepless trigger and ergonomically designed rubber handle for better grip and insulation from cold air and vibration. Features include a patented shock reduction system to give low vibration and a dry shot prevention mechanism to avoid use unless the chisel is engaged.

Stock no		207740101
Chisel holder (round or hexagon)	mm	10.2
Blows*	per minute	2900-3100
Piston stroke	mm	67
Sound level (BS EN 15744)	dB (A)	102.8
Vibration (ISO 8661-9)	m/s ²	4.98
Hose size	inch	3/8
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	636
Air consumption at 20% int*	l/min	127
Air consumption at 100% int*	cfm	24.1
Air consumption at 20% int*	cfm	4.8
Total Length	mm	212
Weight of machine	kg	1.8
Price		€129.70
Spring holder		207740507
Price		€2.40
Quick chuck holder		207740606
Price		€19.80

At 6.2 bar





Air Chisel Hammers

A 10 piece round shank 7" chisel set for use with air chisel hammers. Supplied in a TC tray with removable lid to fit the Teng Tools tool storage system or for use on its own as a storage case.



Stock no		207741000
Chisels	mm	tapered punch, flat 21mm, flat 35mm, spot weld, panel, cut off/ripping
Price		€71.20
Tapered punch chisel		207741109
Price		€5.60
Flat chisel 21mm		207741208
Price		€7.30
Flat chisel 35mm		207741307
Price		€10.50
Spot weld chisel		207741406
Price		€7.70
Panel chisel		207741505
Price		€7.90
Cut off/ripping chisel		207741604
Price		€7.00

Air Chisel Hammers

A 10 piece hexagon shank 7" chisel set for use with air chisel hammers. Supplied in a TC tray with removable lid to fit the Teng Tools tool storage system or for use on its own as a storage case.



Stock no		207741703
Chisels	mm	tapered punch, flat 21mm, flat 35mm, spot weld, panel, cut off/ripping
Price		€76.10
Tapered punch chisel		207741802
Price		€6.00
Flat chisel 21mm		207741901
Price		€7.60
Flat chisel 35mm		207742008
Price		€10.80
Spot weld chisel		207742107
Price		€8.10
Panel chisel		207742206
Price		€8.20
Cut off/ripping chisel		207742305
Price		€7.30



Chisel and Needle Hammer set

A straight chisel and needle hammer set for clearing and cleaning operations such as removing heavy paint, rust scale, welding residue, concrete, etc. The needle hammer is ideal for working on uneven surfaces and the quick chuck enables chisels to be changed easily and quickly. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. A front exhaust and ergonomic grip built in to the handle insulate against cold air and vibration. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes a chisel hammer, 3 chisels, the needle hammer attachment, a mini oiler and hexagon key.

Stock No		200230100
Number of blows*	per minute	4400
Number of needles	pcs	19
Chisel/needle stroke	mm	33
Needle diameter/length	mm	3 x 180
Sound level (chisel/needles)(EN ISO15744)	db (A)	100.5/90.1
Vibration (chisel/needles)(EN28662-1)	m/s ²	2.7/1.6
Hose size	inch	3/8
Connection thread	inch	1/4
Air consumption at 100% int*	l/min	360
Air consumption at 20% int*	l/min	72
Air consumption at 100% int*	cfm	12.7
Air consumption at 20% int*	cfm	2.5
Total length	mm	400
Weight	kg	2.7
Price		€495.00
Flat chisel		200231009
Price		€24.50
Angled chisel		200231108
Price		€24.50
Dressing chisel		200231207
Price		€24.50
Needle attachment (complete)		200231306
Price		€211.00
Needle set 3mm (19 pieces)		200231405
Price		€37.30



Chisel Hammer sets

A straight chisel set for clearing and cleaning operations such as removing heavy paint, rust scale, welding residue, concrete, etc. The quick chuck enables chisels to be changed easily and quickly. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. A front exhaust and ergonomic grip built in to the handle insulate against cold air and vibration. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes a chisel hammer, 3 chisels, a mini oiler and hexagon key.

Stock No		200240109
Number of blows*	per minute	4400
Chisel stroke	mm	33
Sound level (EN ISO15744)	db (A)	100.5
Vibration (EN28662-1)	m/s ²	2.7
Hose size	inch	3/8
Connection thread	inch	1/4
Air consumption at 100% int*	l/min	360
Air consumption at 20% int*	l/min	72
Air consumption at 100% int*	cfm	12.7
Air consumption at 20% int*	cfm	2.5
Total length	mm	340
Weight	kg	1.5
Price		€390.00
Flat chisel		200231009
Price		€24.50
Angled chisel		200231108
Price		€24.50
Dressing chisel		200231207
Price		€24.50





Needle Scalers

A straight needle hammer for clearing and cleaning operations such as removing heavy paint, rust scale, welding residue, concrete, etc. The needle hammer is ideal for working on uneven surfaces. Equipped with 360° swivelling air intake to make the machine easier to use with little interference from the air line. A front exhaust and ergonomic grip built in to the handle insulate against cold air and vibration.



Stock No	200250108	
Number of blows*	per minute	2800
Number of needles	pcs	12
Chisel/needle stroke	mm	24
Needle diameter/length	mm	3 x 126
Sound level (EN ISO15744)	db (A)	88.7
Vibration (EN28662-1)	m/s ²	3.8
Hose size	inch	3/8
Connection thread	inch	1/4
Air consumption at 100% int*	l/min	300
Air consumption at 20% int*	l/min	60
Air consumption at 100% int*	cfm	10.6
Air consumption at 20% int*	cfm	2.1
Total length	mm	305
Weight	kg	1.1
Price	€270.00	
Needle attachment (complete)	200251007	
Price	€75.00	
Needle set 3mm (12 pieces)	200251106	
Price	€24.30	

At 6.2 bar

Engraving pens

A tungsten carbide tip engraving pen for engraving, cleaning, chipping, etc. Features include an adjustable stepless variable speed. Supplied with a 1.5 meter assembled air line with a 360° swivelling air intake to make the machine easier to use with little interference from the air line. Features include a front exhaust and a steel housing with knurled grip and on/off control. With a high working frequency and low vibration the pen is comfortable to use and is suitable for use on materials from hard metal to soft plastic.



Stock no	207940107	
Working pressure	bar	6
number of strokes adjustable up to	rpm	36000
Sound level (CEN/TC 255 N81)	dB (A)	90
Vibration (ISO 5349)	m/s ²	<2.5
Air inlet	inch	1/4
Air consumption at 100% int*	l/min	30
Air consumption at 50% int*	l/min	15
Air consumption at 100% int*	l/s	0.5
Air consumption at 50% int*	cfm	0.6
Weight	kg	0.22
Price	€110.00	
Replacement engraving tip	207940503	
Price	€18.30	

At 6.2 bar



Air blow guns

A handy set including 3 different air blow guns with interchangeable accessories. Each of the blow guns features a 360° swivelling air intake to make the machine easier to use with little interference from the air line and a hanging hook facility. Stepless triggers and ergonomically designed handles for better grip and insulation from cold air and vibration which are suitable for left and right handed users. Supplied in a handy carrying case with recessed handle, click lock mechanism and rubber feet. The set includes various tips including adjustable, extension type, brass, ball pump, needle, rubber, air screen, nylon, safety booster, swivelling and car tyre inflator types.

Stock no		208080101
Air inlet	inch	¼
Number of pistols	pcs	3
Number of tips	pcs	19
Maximum working pressure	bar	11-15
Sound level	dB(A)	85-90
Air consumption*	l/min	115-160
Air consumption*	cfm	23-32
Weight	kg	0.85
Price		€120.00
Accessories		
Air blow gun plastic changeable type		208080507
Price		€9.00
Brass tip		208080606
Price		€1.60
Safety tip (short type)		208080705
Price		€1.60
Safety tip (long type)		208080804
Price		€2.50
½" rubber tip		208080903
Price		€5.10
1" rubber tip		208081000
Price		€6.20
1 ¾" rubber tip		208081109
Price		€6.90
Adjustable tip		208081208
Price		€4.10
Tyre inflator adaptor		208081307
Price		€4.80
Air screen tip		208081406
Price		€2.50
Ball pump tip		208081505
Price		€2.30
3" nylon tip		208081604
Price		€2.50
1 ⅙" needle tip		208081703
Price		€3.70
2 ⅝" needle tip		208081802
Price		€4.10
4" needle tip		208081901
Price		€6.90
4" extension tip		208082008
Price		€4.60
13" extension tip		208082107
Price		€6.90
20" angle swivel with telescopic tube		208082206
Price		€18.00
4" adjustable tip		208082305
Price		€6.40
13" adjustable tip		208082404
Price		€8.70



Fluid chip shield		208082503
Price		€3.60
Safety tip		208082602
Price		€3.60
Turbo tip		208082701
Price		€8.40

At 6.2 bar

All prices exclude VAT and are subject to availability



Miscellaneous Air Tools

Air Blow Guns

A plastic, pistol type air blow gun with an ergonomic grip and stepless trigger which is suitable for both left and right handed users. Equipped with a hanging hook, 90mm bent aluminium spray tube with slotted safety tip and a 360° swivelling air intake to make the machine easier to use with little interference from the air line.



Stock no	207970104	
Air inlet	inch	¼
Max working pressure	bar	11
Sound level	dB (A)	85-90
Air consumption at 100% int*	l/min	160
Air consumption at 20% int*	l/min	32
Air consumption at 100% int*	l/s	2.7
Air consumption at 20% int*	l/s	1.1
Total length	mm	260
Weight	kg	0.10
Price	€8.50	

At 6.2 bar

Aluminium pistol style air blow guns with an ergonomic grip and stepless trigger which are suitable for both left and right handed users. Equipped with a hanging hook and a 360° swivelling air intake to make the machine easier to use with little interference from the air line. Two models are available giving a choice of short adjustable nozzle or a 100mm tube nozzle.



Stock no	207980103	207980202
Air inlet	inch ¼	¼
Max working pressure	bar 15	15
Sound level	dB (A) 85-90	85-90
Air consumption at 100% int*	l/min 140	160
Air consumption at 20% int*	l/min 28	32
Air consumption at 100% int*	l/s 2.3	2.7
Air consumption at 20% int*	l/s 1	1.1
Length	mm 115	200
Weight	kg 0.24	0.24
Price	€17.20	€17.70

At 6.2 bar

Straight style air blow guns with an ergonomic grip and stepless trigger which are suitable for both left and right handed users. Equipped with a finger stop, a hanging hook and a 360° swivelling air intake to make the machine easier to use with little interference from the air line. Two models are available giving a choice of short adjustable nozzle or a 100mm tube nozzle.



Stock no	207990102	207990201
Air inlet	inch ¼	¼
Max working pressure	bar 15	15
Sound level	dB (A) 85-90	85-90
Air consumption at 100% int*	l/min 115	130
Air consumption at 20% int*	l/min 23	26
Air consumption at 100% int*	l/s 1.9	2.2
Air consumption at 20% int*	l/s 0.8	0.9
Length	mm 140	230
Weight	kg 0.2	0.2
Price	€11.70	€12.30

At 6.2 bar

Combined vacuum and blow gun

The innovative Luna cleaner gun is one tool with two functions, suction and blowing. Ideal for cleaning around machines in your work shop as well as use as a vacuum cleaner. Instead of blowing dust around you can first suck most of it up and just blow away any residue which is hard to suck. One hand operation. Press firmly and you start the suction function, depress the trigger further and the cleaner gun starts blowing. The "one time use dust bag" is covered by the recoil hose which is included as standard. The small weight (595gm) makes it comfortable to use by one hand, dimensions 327 x 114 x 53mm. Suction 600 l/min and blowing 300 l/min at 8 bar



Stock no	204060107	
Connection thread	¼	
Air consumption/l/min	350	
Total length	mm 340	
Weight	kg 0.2	
Price	€95.00	
Dust Bag	204060206	
Price	€2.50	

All prices exclude VAT and are subject to availability



Sand Blasting guns

Professional quality sand blasting gun. A very efficient tool for use against small rust spots. It is supplied with four different nozzles, three templates and a dust bag. It is suitable for aluminium silicate and aluminium oxide. Features include a comfortable grip and swivelling air intake. Comes complete in a double tool storage tray for use in the Teng Tools storage system.

Stock no	208710103	
Air inlet	inch	¼
Max.working pressure	bar	10
Working pressure	bar	6-7
Air consumption at 100% int*	l/min	340
Air consumption at 20% int*	l/min	68
Air consumption at 100% int*	cfm	12.0
Air consumption at 20% int*	cfm	2.4
Rec.max grain size	mm	0.5
Sound level	dB(A)	90
Weight	kg	0.8
Price	€49.90	



Air Spray Guns

Gravity feed pistol with adjustable fluid output, pattern width and working pressure. Ergonomic grip. Low sound level. High capacity. 360° swiveling air intake. Developed for professional workshop applications. Suitable for automotive use, metallic products, coat and primer surface, anti rust paint etc.

Stock no		208020107	208020206	208020305	208020404	208020503	208020602
Paint nozzle	mm	1.0	1.3	1.5	1.8	2.0	2.5
Working pressure	bar	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0
Max.fluid output	l/min	0.25	0.25	0.25	0.25	0.25	0.25
Max. pattern width	mm	245	245	245	245	245	245
Air inlet		¼	¼	¼	¼	¼	¼
Air consumption at 100% int*	l/min	300	300	300	300	300	300
Air consumption at 15% int*	l/min	45	45	45	45	45	45
Air consumption at 100% int*	cfm	10.6	10.6	10.6	10.6	10.6	10.6
Air consumption at 15% int*	cfm	1.6	1.6	1.6	1.6	1.6	1.6
Cup capacity	l	0.6	0.6	0.6	0.6	0.6	0.6
Weight	kg	0.5	0.5	0.5	0.5	0.5	0.5
Price /bar		€119.90	€119.90	€119.90	€119.90	€119.90	€119.90



Suction feed pistol with adjustable fluid output, pattern width and working pressure. Ergonomic grip. Low sound level. High capacity. 360° swivelling air intake. Developed for professional workshop applications. Suitable for automobiles, metallic products, coat and primer surface, anti rust paint etc.

Stock no		208010108	208010207	208010306	208010405	208010504	208010603	208010702
Paint nozzle	mm	1.0	1.3	1.5	1.8	2.0	2.5	3.0
Working pressure	bar	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0	2.6-3.0
Max.fluid output	l/min	0.22	0.22	0.22	0.25	0.25	0.25	0.25
Max. pattern width	mm	245	245	245	245	245	245	245
Air inlet		¼	¼	¼	¼	¼	¼	¼
Air consumption at 100% int*	l/min	300	300	300	300	300	300	306
Air consumption at 15% int*	l/min	46	46	46	46	46	46	46
Air consumption at 100% int*	cfm	10.8	10.8	10.8	10.8	10.8	10.8	10.8
Air consumption at 15% int*	cfm	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Cup capacity	l	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Weight	kg	0.45	0.45	0.45	0.45	0.45	0.45	0.45
Price		€195.00						